

# HONDA

## HONDA GX200 HORIZONTAL ENGINE



Engine Type	Air-cooled 4-stroke OHV
Bore x Stroke	68 X 54 mm
Displacement	196 cm <sup>3</sup>
Net Power Output*	5.5 HP (4.3 kW) @ 3,600 rpm
Net Torque	9.1 lb-ft (12.4 Nm) @ 2,500 rpm
PTO Shaft Rotation	Counter clockwise (from PTO shaft side)
Compression Ratio	8.5:1
Lamp/Charge coil options	25W, 50W / 1A, 3A, 7A
Carburetor	Butterfly
Ignition System	Transistorized magneto
Starting System	Recoil Starter
Lubrication System	Splash
Governor System	Mechanical
Air cleaner	Dual element
Oil Capacity	0.63 US qt (0.6l)
Fuel Tank Capacity	3.3 U.S. qts (3.1 liters)
Fuel	Unleaded 86 octane or higher
Dry Weight	35 lbs. (16 kg)

Honda's GX series engines are legendary for superior reliability and performance. And there's no doubt about it: the GX200 lives up to the legend. Lower noise levels, lower vibration, and lower emissions – without sacrificing power output or performance.

### HONDA ORIGINAL & REPLACEMENT SPARES AVAILABLE

PTO Shaft Options	
GX200 H2 QX	Parallel keyed 3/4" shaft
GX200 UT QC9	3/4" Keyed shaft (Cyclone filter)
GX200 H2 VX	Tapered shaft engine (Generator)
GX200 UT QXE4	Parallel Keyed 3/4" shaft, electric start

## TURFMASTER, YOUR HONDA AGENT FOR SOUTH AFRICA

\*The SAE J1349 standard measures net horsepower with the manufacturer's production muffler and air cleaner in place. Net horsepower more closely correlates with the power the operator will experience when using a Honda engine powered product. The power rating of the engines indicated in this document measures the net power output at 3600 rpm (7000 rpm for model GXH50, GXV50, GX25 and GX35) and net torque at 2500 rpm, as tested on a production engine. Mass production engines may vary from this value. Actual power output for the engine installed in the final machine will vary depending on numerous factors, including the operation speed of the engine in application, environmental conditions, maintenance and other variables.

NOTE: Specifications may vary according to the types, and are subject to change without notice.

# TURFMASTER

(PTY) LTD

HEAD OFFICE: NIGEL, GAUTENG  
1 Third Ave, Vorsterskroon  
Tel: 011 730 3400 / Fax: 011 814 2345  
Email: [info@turfmaster.co.za](mailto:info@turfmaster.co.za)  
Website: [www.turfmaster.co.za](http://www.turfmaster.co.za)

#### BRANCHES:

**Bellville**  
Cnr Cilmore & Labelle Rd,  
Stikland, Bellville  
Tel: (021) 945-4106/7/8  
Fax: (021) 946-2371  
Email: [gpl@turfmaster.co.za](mailto:gpl@turfmaster.co.za)

**Durban/Pinetown**  
Factory 6, 14 Livingstone Road,  
New Germany, Pinetown  
Tel: (031) 701 8233  
Fax: (031) 701 3097  
Email: [romona@turfmaster.co.za](mailto:romona@turfmaster.co.za)

**Port Elizabeth**  
20 – 6th Ave.,  
Walmer, Port Elizabeth  
Tel: (041) 581-8443/4/5  
Fax: (041) 581-8446  
Email: [geraldene@turfmaster.co.za](mailto:geraldene@turfmaster.co.za)

**Pretoria**  
Unit 9 Miracle Park, Lenchen Ave  
Ext off Old JHB Road, Centurion  
Tel: (012) 653-8342/8  
Fax: (012) 653-8343  
Email: [dennismow@mweb.co.za](mailto:dennismow@mweb.co.za)